

Data Sheet

Cylinders - Square Profile Cylinders

A24050125O

A24 Series - Double Acting Cylinder



Technical Specification

Product Description	DA 50 x 125 SQ Cyl. Basic
Large Description	• A24050125O • DA 50 x 125 SQ Cyl. Basic • Non-Magnetic • Adjustable cushioning at both ends
Cylinder Bore {mm}	050
Stroke {mm}	125
Cushioning Stroke (mm)	023
Piston Rod Diameter (mm)	020
Medium Temperature °C	5 °C to 50 °C
Medium Temperature °F	41 °F to 122 °F
Mode of Operation	Double Acting
Dimensional Standard	ISO 15552 / VDMA 24674
Cushioning Method	Adjustable cushioning at both ends
Functional Variable	Standard
Position Detection	Non-Magnetic
Materials of Construction	Aluminium, Brass, Steel, Acetal, Polyurethane, Nitrile (Regular)
Pneumatic Connection	G1/4
Piston rod Thread Size	M16 x 1.5
Theoretical force at 0.6 MPa(6 Bar,87 PSI), Retract stroke (Force in N) 1N = 0.1 kgf	891

Theoretical force at 0.6 MPa(6 Bar,87 PSI), Extend stroke (Force in N) 1N = 0.1 kgf	1060
Seal Kit Part Number	SK0053
Optional Features	Basic
Optional Mountings	Basic
Optional Accessories	None
Connectors	• R1/4 x Dia 8-OD Tubing • R1/4 x Dia 10-OD Tubing
Tubes	Dia 8 & Dia10
Flow Control Valves	• R1/4 x Dia 8-OD Tubing • R1/4 x Dia 10-OD Tubing
Catalogue Dim L (mm)	304
Catalogue Dim B (mm)	64
Basic weight for 0 mm stroke	Nil
Additional weight per 10 mm stroke	Nil
Additional weight per mm stroke[kilograms]	Nil
Product Weight [kilograms]	1.9
Product Weight [pounds]	4.19
Package size L x B x H (mm)	Nil
Package size L x B x H (inch)	Nil
Operating Medium	Compressed air – Filtered – Lubricated
Ambient Temperature °C	-10 °C to +60 °C
Ambient Temperature °F	14 °F to 140 °F
Cylinder Type	Square Profile Cylinder
Cushion Pad	Elastomer
Piston-rod end	Male Thread
Magnetic Sensor	Not Applicable
Working Pressure (bar)	0.5 to 10
Working Pressure (psi)	7.25 to 145
Working Pressure (MPa)	0.05 to 01
Variants	Piston rod at one end

Features	• Adjustable cushioning at both ends with elastomer pads • Wide varieties of mountings • Magnetic and Non magnetic version • Low Friction (Optional) • Aluminium profile (square) cylinder barrel • Magnetic sensor common for all sizes (Refer Magnetic sensor catalogue) • Optional - High temperature (FKM seals) 150°C max. ** • Optional - Non corrosive Stainless steel piston rod and piston rod lock nut (SS 304) **
Shelf Life	Nil
Temperature Storage Range Low °C	-10 °C
Temperature Storage Range Low °F	14 °F
Temperature Storage Range High °C	+60 °C
Temperature Storage Range High °F	140 °F
REACH	Nil
ROHS	Nil
Type of Mountings	Basic cylinder, Foot mounting, Front flange, Rear flange, Male clevis, Male clevis (with spherical bearing), Female clevis, Female clevis (King pin), Front trunnion, Rear trunnion,
Type of Accessories	Clevis foot bracket, Clevis foot bracket (spherical) , Wall mounting bracket, Trunnion bracket, Rod end fork, Rod end aligner, Rod end spherical eye
HSN Code	84123100
Unit of Measurement	No's
Minimum Order Quantity	1
Is this part Made-to-Order?	Yes
Inner Package Quantity	1
Manufacturer Name	Janatics India Private Limited
Brand Name	Janatics
Countries of Origin	India

Note

For Non standard or longer stroke cylinders, contact your Regional office or Regional dealer or Janatics India ** - Refer Special Ordering number # - Applicable only for standard strokes (Upto 500mm)