

Data Sheet

Directional Control Valve - Compact Valves

DS254SS60-W

DS2-5/2 Double Solenoid Operated - DS2-5/2
Double Solenoid Operated



Technical Specification

Product Description	Double Solenoid Pilot Operated Valve - G1/8, 5 Port 2 Way, 24V DC
Large Description	• DS254SS60-W • Double Solenoid Pilot Operated Valve - G1/8, 5 Port 2 Way, 24V DC • Standard Socket
HSN Code	84818050
Design Type	DS2-Spool Type
Valve Type	Pilot Operated Valve
Number of Port and Positions	5 Port 2 Way
Mode of Actuation	Solenoid
Mode of Reset	Solenoid
Flowrate in LPM (Inlet to outlet port)	450
Flowrate in CFM (Inlet to outlet port)	15.9
Thread Type	BSP(G)
Port Size	G1/8
Outlet Port (2)	G1/8
Outlet Port (4)	G1/8
Exhaust (3)	G1/8
Exhaust (5)	G1/8
Manual Override	Push and Turn to Lock

Operating Medium	Compressed Air Dry, Filtered, Lubricated
Operating Pressure Range {bar}	2 to 8
Operating Pressure Range (psi)	29 to 116
Operating Pressure Range (Mpa)	0.2 to 0.8
Coil Voltage Type	DC
Voltage Rating {+/-10%}	24V
Power Consumption	2.5W
Coil Width	17 MM
Coil Type	Standard
Socket Type	Standard Socket
Coil Connection Type	PG7 (cable OD 4 - 6 mm)
Catalogue Dim L (mm)	176
Catalogue Dim B (mm)	18
Catalogue Dim H (mm)	57
Product Weight [kilograms]	0.1815
Product Weight [pounds]	0.40
Package size L x B x H (mm)	Nil
Gross Product Weight [kilograms]	Nil
Gross Product Weight [pounds]	Nil
Seal Kit Part Number	SK4069
Actuator Assembly	SC3002
Coil (without Connector)	DC36W
Modular solenoid valve	Not Applicable
Connectors	• R1/8 x Dia 6-OD Tubing • R1/8 x Dia 8-OD Tubing
Tubes	Dia 6 & Dia 8
Flow Control Valves	• R1/8 x Dia 6-OD Tubing • R1/8 x Dia 8-OD Tubing
Product Group	Directional Control Valve
Ambient Temperature °C	-10 °C to +60 °C
Ambient Temperature °F	14 °F to 140 °F
Medium Temperature °C	5 °C to 50 °C
Medium Temperature °F	41 °F to 122 °F
Materials of Construction	Aluminium, Nitrile, Brass, Acetal, PBT, Zinc, Stainless Steel, Polyamide, Viton

Mounting Type	Individual, Manifold Mountable
Class of Insulation	Class F
Duty Cycle	Continuous
Type of Coil Protection	IP 65
Features	• Suitable for manifold mounting • Mounting position for individual unit • Compact size • Manual override • Wide range of manifolds available • Wide range of coil voltages
Note	At Inlet Pressure 6 bar (87 psi, 0.6 MPa), and pressure drop $\Delta p = 1$ bar (145 psi, 0.1 MPa)
Unit of Measurement	No's
Minimum Order Quantity	1
Is this part MadetoOrder?	Yes
Inner Package Quantity	1
Manufacturer Name	Janatics India Pvt.Ltd
Brand Name	Janatics
Countries of Origin	India
Temperature Storage Range Low °C	-10 °C
Temperature Storage Range Low °F	14 °F
Temperature Storage Range High °C	60 °C
Temperature Storage Range High °F	140 °F
ATEX	Nil
REACH	Nil
ROHS	Nil