



**HYDAC INTERNATIONAL GmbH**

66280 Sulzbach/Saar

Germany

**Phone:** +49 (0) 68 97 509-01

**Email:** [info@hydac.com](mailto:info@hydac.com)

**Website:** [www.hydac.com](http://www.hydac.com)

## Part Number 1260904, HYDAC Filter Elements - Type D For Pressure Filters



List Price —

QUOTE

### Specifications | Dimensions

#### Specifications

|                               |                              |
|-------------------------------|------------------------------|
| <b>Model Code</b>             | 0160 D 003 ON                |
| <b>Absolute Filter Rating</b> | 3 µm                         |
| <b>Media Type</b>             | ON=Optimicron low-press.     |
| <b>Seal</b>                   | Nitrile Rubber (NBR)         |
| <b>Cap 1 Type</b>             | O-Ring Cap                   |
| <b>Cap 2 Type</b>             | Closed End Cap               |
| <b>Type</b>                   | Hydraulic Filter Element     |
| <b>Size</b>                   | 0160                         |
| <b>Style</b>                  | Cartridge                    |
| <b>Filter Material</b>        | Microglass                   |
| <b>Configuration</b>          | One Open Cap, One Closed Cap |
| <b>Cap 1 Material</b>         | Steel                        |
| <b>Cap 2 Material</b>         | Aluminum                     |
| <b>Support Tube Material</b>  | Steel                        |
| <b>Outer Sleeve</b>           | Yes                          |
| <b>Flow Direction</b>         | Outside - In                 |
| <b>Beta Rating</b>            | $\beta_3 > 1000$             |
| <b>Collapse Rating</b>        | 20.000 bar                   |
| <b>Stat-Free</b>              | No                           |
| <b>K-Factor</b>               | 0.604 psi/gpm                |

|                      |                               |        |
|----------------------|-------------------------------|--------|
| Minimum Temperature  | -30 °C                        |        |
|                      | -22 °F                        |        |
| Maximum Temperature  | 100 °C                        | 212 °F |
| Efficiency           | 99.9 %                        |        |
| BUn                  | EA                            |        |
| Division             | HYDRAULIC AND LUBE FILTERS    |        |
| Product Group Family | ELEMENTS-HYDAC<br>PROPRIETARY |        |
| Product              | HYDAC ELEMENTS                |        |

|                  |          |        |
|------------------|----------|--------|
| Dimensions       |          |        |
| Outside Diameter | 2.7 in   | 69 mm  |
| Length           | 4.6 in   | 117 mm |
| Inside Diameter  | 34 mm    |        |
|                  | 1.339 in |        |