



NX-AD3203

4 Analog Inputs, 4 to 20 mA single ended, resolution 1:8000, 250 μ s/ch, screwless push-in connector, 12 mm wide

Specifications

I/O system	NX I/O Bus
Type of module	Analog I/O
Number of analog inputs	4
Temperature input type	None
Linear analog input type	4 to 20 mA
Resolution of the analog inputs	13 Bit
Input circuit type	Single-ended
Number of analog outputs	0
Linear analog output type	None
Resolution of the analog outputs	0 Bit
Conversion time	1 ms/unit
Signal processing	Free running
IO-Link master	✗
I/O connection type	Push-in
Number of I/O connectors	1
Detachable I/O terminal block	✓
Suitable for safety functions	✗
SIL according to IEC 61508	None
Degree of protection (IP)	IP20
Product Height (unpacked)	104.5 mm
Product Width (unpacked)	12 mm
Product Depth (unpacked)	80.1 mm
Product Weight (unpacked)	70 g

Accessories



NX-AUX02

Terminal block coding pins for 10x NX I/O units (terminal block: 30 pins, unit: 30 pins)

Spare parts



NX-TBA122

Replacement screwless push-in connector with 12 wiring terminals (marked A+B)

CAD Library



IO-Link Series Brochure

EN PDF 7.95 MB



Machine Safety Solution Brochure

EN PDF 2.86 MB



NX-CT High-speed Counter Unit Brochure

EN PDF 863 KB



NX-HAD Brochure

EN PDF 1.22 MB



NX-HTC/NX-TC/EJ1/E5DC-B Temperature control units Flyer

EN PDF 3.28 MB



NX-series Analog I/O Unit - NX-AD/DA Datasheet

EN PDF 5.68 MB



NX-series Analog I/O Units Users Manual

EN PDF 7.31 MB



NX-series I/O system Brochure

EN PDF 8.63 MB



Omron GX-JC0x-x EtherCAT Junction Box EtherCAT ESI file

EN ZIP 3.36 KB



Omron NX-ECC20x EtherCAT ESI file

EN ZIP 1.51 MB



Sysmac Catalogue

EN PDF 43.5 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 12 MB