



NX-SL3300

Safety controller, 32 safety master connections, up to 256 safety I/O

Specifications

I/O system	NX I/O Bus
Type of module	Safety control
Number of digital inputs	0
Number of digital outputs	0
Number of analog inputs	0
Number of analog outputs	0
Signal processing	Synchronous
IO-Link master	✗
Suitable for safety functions	✓
SIL according to IEC 61508	3
Communication port(s)	None
Memory size	512 kByte
Product Height (unpacked)	100 mm
Product Width (unpacked)	30 mm
Product Depth (unpacked)	71 mm
Product Weight (unpacked)	75 g

CAD Library



IO-Link Series Brochure

EN PDF 7.95 MB



Machine Safety Solution Brochure

EN PDF 2.86 MB



NX Series Safety Control Unit Users Manual

EN PDF 40 MB



NX Series Safety Control Unit Instructions Reference Manual

EN PDF 2.05 MB



NX-CT High-speed Counter Unit Brochure

EN PDF 863 KB



NX-HAD Brochure

EN PDF 1.22 MB



NX-HTC/NX-TC/EJ1/E5DC-B Temperature control units Flyer

EN PDF 3.28 MB



NX-SL3 Safety CPU Unit Datasheet

EN PDF 2.42 MB



NX-series Reference Manual

EN PDF 1.45 MB



NX-series I/O system Brochure

EN PDF 8.63 MB



Omron NX-ECC20x EtherCAT ESI file

EN ZIP 1.51 MB



Sysmac Catalogue

EN PDF 43.5 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 12 MB