



NX-SOD400

4 Digital Safety Outputs, PNP 24 VDC, 0.5 A/point, 2.0 A/NX Unit, screwless push-in connector, 12 mm wide

Specifications

I/O system	NX I/O Bus
Type of module	Safety I/O
Number of digital inputs	0
Digital input type	None
Number of digital outputs	4
Digital output type	PNP
Permitted voltage at output	20.4-28.8 V
Output current	0.5 A
Short-circuit protected outputs	✗
Connection method	4-wire
Signal processing	Free running
IO-Link master	✗
I/O connection type	Push-in
Number of I/O connectors	1
Detachable I/O terminal block	✓
Suitable for safety functions	✓
SIL according to IEC 61508	3
Communication port(s)	None
Number of IOV (V+) terminals	0
Number of IOG (V-) terminals	4
Number of COM terminals	0
Degree of protection (IP)	IP20
Product Height (unpacked)	104.5 mm

Product Width (unpacked)	12 mm
Product Depth (unpacked)	80.1 mm
Product Weight (unpacked)	90 g

Accessories



NX-AUX02

Terminal block coding pins for 10x NX I/O units (terminal block: 30 pins, unit: 30 pins)

Spare parts



NX-TBA082

Replacement screwless push-in connector with 8 wiring terminals (marked A+B)

CAD Library



IO-Link Series Brochure

EN PDF 7.95 MB



Machine Safety Solution Brochure

EN PDF 2.86 MB



NX Series Safety Control Unit Users Manual

EN PDF 40 MB



NX-CT High-speed Counter Unit Brochure

EN PDF 863 KB



NX-HAD Brochure

EN PDF 1.22 MB



NX-HTC/NX- TC/EJ1/E5DC-B Temperature control units Flyer

EN PDF 3.28 MB



NX-SI/SO Safety I/O Unit Datasheet

EN PDF 2.62 MB



NX-SL3 Safety CPU Unit Datasheet

EN PDF 2.42 MB



NX-series Reference Manual

EN PDF 1.45 MB



NX-series I/O system Brochure

EN PDF 8.63 MB



Omron GX-JC0x-x EtherCAT Junction Box EtherCAT ESI file

EN ZIP 3.36 KB



Omron NX-ECC20x EtherCAT ESI file

EN ZIP 1.51 MB



Sysmac Catalogue

EN PDF 43.5 MB



Sysmac: A Fully Integrated Platform Brochure

EN PDF 12 MB