


Dk-Lok USA

161 West I-65 Service Road

Mobile, AL 36608

Phone: (251) 472-9580


Fax: (251) 450-0962 or (800) 287-8186

info@dklokusa.com

Item # V16C-F-12N-S, V16 Series Severe Service Union Bonnet Valves

Features

- Pressure up to 6000 psig (413 bar) @ 100°F (38 °C).
- High Temperatures up to 449°F (232C) with standard PTFE packing; up to 1200°F (648°C) with Grafoil packing.
- Standard 316 stainless steel, optional Alloy 20, and Alloy C276 construction.
- Valve stem back seating against the bevelled edge of bonnet in fully open position prevents maximum leakage through bonnet when packing fails.
- Standard non-rotating stem disc and stem packing below the threads design.



[Specifications](#) | [Dimensions](#)

Specifications

Series	11.1 mm Orifice
End Connection	Female NPT
Size Inlet x Outlet	3/4" Female NPT x 3/4" Female NPT
Valve Pattern	Inline
Packing Material	PTFE
Stem Disc	Globe
Handle	SS316 Bar Handle

Sour Gas	No Sour Gas
Valve Material	Stainless Steel 316

Dimensions

Orifice	11.1
Cv	2.2
L	82.6 mm
L1	41.1 mm
B1	48.5 mm
A1	19.8 mm
H	88.9 mm
G	26.2 mm
D	124.0 mm