

## **A-10 ; 0...2.5 bar gauge; 4...20 mA, 2-W @ 8...30 V DC**

### Pressure transmitter Model A-10

Item number: 12742423

Quantity: 1 pcs.

Overview: A-10 ; 0...2.5 bar gauge; 4...20 mA, 2-W @ 8...30 V DC  
Pressure transmitter Model A-10  
Non-linearity: 0.5% BFSL  
Process connection: G 1/4 A DIN EN ISO 1179-2; Sealing: NBR  
Electrical connection: circular connector M12x1, 4-pin  
Pin assignment: U+=1, U-=3  
Permissible medium temperature: 0...+80 °C  
Approvals: cULus  
Type of packaging: folding box single  
WIKA standard - specification according to data sheet PE 81.60

Details: Pressure transmitter Model A-10  
for general applications  
Specifications according to data sheet: PE 81.60  
Wetted parts: 316L  
Case: 316L  
Non-linearity: 0.5% BFSL  
Unit: bar  
Pressure type: gauge  
Measuring range: 0...2.5 bar gauge  
Process connection: G 1/4 A DIN EN ISO 1179-2  
Sealing: NBR  
Permissible medium temperature: 0...+80 °C  
Output signal: 4 ... 20 mA, 2-wire  
Power supply: 8...30 V DC  
Electrical connection: circular connector M12x1, 4-pin  
Approvals: cULus  
Customer address: [www.wika.com](http://www.wika.com)  
Model name customer-specific: A-10  
Type of packaging: folding box single  
Pin assignment: U+=1, U-=3  
Customer-specific: WIKA standard - specification according to data sheet  
Model: A-10 2.0  
Operating Instructions: with printed OI  
Additional Data: without