

232.34.4 1/2" 5000 psi 2nd scale bar 1/2 NPT lower mount

Process Gauge

Item number: 50095595

Quantity: 1 pcs.

Overview: 232.34.4 1/2" 5000 psi 2nd scale bar 1/2 NPT lower mount
Measuring System 316L
Ingress protection: IP 65
+/- 0.5% ASME B40.100 Grade 2A
Window: laminated safety glass
adjustable pointer
Case filling fluid: prepared for filling
Restrictor: stainless steel, D 0.6
Pressure Gauge Standard: US-Standard
2nd scale red
stop-pin at 6 o'clock
WIKA® Serial number *...*
with QR Code
316 SS Tube and Connection
Label: WIKA standard without / with Tag-number

Details: Process Gauge
Model: 232.34
Specifications according to data sheet: PM 02.10
Case: Black Fiberglass Reinforced Thermoplastic (Pocan B4225)
Bezel ring: Threaded, Black Fiberglass Reinforced Thermoplastic (Pocan B4225)
Measuring system: stainless steel
Case filling: without
Nominal size: 4 1/2"
Scale range: 0...5000 psi
2nd Scale or Special Scale: 2nd scale bar
Process connection: 1/2 NPT
Connector location: lower mount
Window: laminated safety glass
Restrictor: stainless steel, D 0.6
Pointer: adjustable pointer
Accuracy class: +/- 0.5% ASME B40.100 Grade 2A
Material pressure element: Measuring System 316L
Case filling fluid: prepared for filling
Ingress protection: IP 65
Dial description:
Pressure Gauge Standard: US-Standard
color for 1.scale (outside): black
color for 2.scale (inside): red RAL 3020
dial background: White
WIKA®

Date: 31/01/2026



serial number on dial: Serial number *...*

QR code with extended serial number on dial

stop pin on dial: at 6 o'clock